

## **PSB - 2160X**

## **Power Surge Block**

The PSB-2160X is a 2160 joule, 8 outlet subscriber premise surge suppressor. The PSB-2160 provides protection for set top boxes, modems and subscriber connected equipment.

Reduce Complaints

Many subscribers have no form of surge suppression on their TVs and Computers. When a surge enters through the power line and harms the subscriber's TV who do they call to complain to ,The Cable Company. Installation of the PSB-2160X will eliminate most of these types of complaints.

## **FEATURES**

- 144000 AMPS maximum spike current
- Full 3 line surge protection
- 2160 Joules
- EMI/RFI noise filter
- 8 AC outlets
- 15 amp overload resettable circuit breaker
- Cable Innovations' quality, reliability and support

Specifications subject to change without notice.



Technical Specifications	
Electrical Rating :15A, 125 VAC, 60Hz, 1800 Watts	Surge Lines Protected (3-Line) : (L-N, L-G, N-G)
Clamping Voltage : L-N 400V , L-G 400V , N-G 500V	Surge Energy Joule Rating: 2160 Joules
Maximum Spike Current :144000A (3 Line Total)	Response Time :<1 Nanosecond
Maximum Spike Voltage : 6KV	EMI/RFI Noise Filter Frequency :150KHz~100MHz
Attenuation : Up to 60dB	TEL/FAX Protection Jack Type : RJ11

